

MC 4000/3000 TP

KEY FEATURES & BENEFITS

- 3000lb or 4000lb lifting capacity based on configuration
- 13 ft. deck with the 3000lb configuration
- Can be installed as material only
- Small footprint
- Simple installation with easy tie-ins, minimal impact on the structure
- Ability to control the hoist from the ground, car, or the landings
- Lower voltage requirements: Common 208v / 3 Φ
- Side and / or front loading basket
- Accessibility to each floor
- Delivers personal and materials at a quick 40fpm
- Can deliver 12' drywall or bundles of scaffold

INDUSTRIES SERVED

Scaffolding • Masonry

Restoration & Renovation • Glazing / Panels
 Drywall







Contact Beta Max today
to discuss your project, or get a quote.
www.BetamaxHoist.com (800) 644-6478

* All Beta Max Hoist Systems meet or exceed ANSI & OSHA specifications. This information is intended to be informative only, and does not constitute a representation or warranty with regard to Beta Max Hoists or any products or services provided. Prices and information are subject to change. Some or all of the renderings in these materials may vary from the actual hoists.

Rev. 05-2016



MAX CLIMBER 4000/3000

SPECIFICATIONS

Lift Capacity	4000 lbs or 3000 lbs
Lift Speed	40 fpm
A/C Power	3 \$\psi 208v
Basket Dimensions	52"x 86" and 52"x 154"

100amp service (fuse disconnect) required up to 20 feet from the installed hoist location





