

H: 220ft/110ft

Capacity: 1000lbs/2000lbs

KEY FEATURES

- Ideal for heavy-duty, high lift projects
- Long lasting performance with minimum maintenance required
- Confined and hard to reach spaces made easy with a portable hoist
- Safe and efficient alternative to rope & pulley systems, cranes, and forklifts
- Installs easily on existing scaffold systems, work platforms, I-Beams, and rooftop mounting options
- Easy Cable Replacement (Beta Max™ provides clamps and crimp)
- I-BEAM TROLLEY TOP Mounting System easily adapts to existing I-Beams onsite



SAFETY FEATURES

- Water Tight Connectors
- Failsafe brake holds the load securely when not lifting or lowering: loads are powered up and down, no free-falling or slipping
- Non-rotating cable helps keeps loads from spinning
- Upper-limit Switch Assembly stops the hoist instantly when activated
- Sturdy Electrical Controller equipped with thermal overload sensing device

INDUSTRIES SERVED

- Scaffolding • Masonry • Stucco
- Glazing • Demolition • Restoration • Construction

Contact Beta Max today to discuss your project, or get a quote.

www.BetamaxHoist.com

(800) 644-6478

SPECIFICATIONS

Set Up	Single Line	Double Line
Lift Capacity	1,000 lbs	2,000 lbs
Lift Speed	80 fpm	40 fpm
Lift Height	220'	110'
A/C Power	220VAC, 20A, 1ϕ	
Horsepower	2HP	
Mounting Options	Fixed I-Beam, I-Beam Trolley, Scaff-Trac and Trestle Monorail	


MOUNTING OPTIONS




Scaff-Trac



Trestle Monorail



Fixed I-Beam



I-Beam Trolley



I-BEAM TROLLEY TOP

ACCESSORIES

- Block Fork • Scaffold Frame Fork • Equipment Basket
- Dumpster Bucket • Spreader Bar • Mud Tub • Double Rope Kit
- Counterweight Clamp Assembly • Remote Control Extension
- Power Cord Extension • Wireless Dual Control Package • Booster Transformer

Contact Beta Max today to discuss your project, or get a quote.